

F6 - F9 SERIES

THE BEST FRAME FOR YOUR REQUEST

BHL



The easiest way to fix a hydraulic breaker on a backhoe loader. FRD has for each backhoe the right setting.

FLAT TOP



The cheapest solution is to attach the breaker with different systems. With the FT framework easy to grow, you have the base mounting plates for quick-change systems of all kinds.

SILENCE



Noise reduction is required in the workplace; you have the beginning of our silent part of our offered possibilities. The frame is up to 6 DbA quieter than the standard frame.


SILENCE



The F9 is only in a LN Frame. The standard or special housing can be made on request.

Features and Benefits:

- Nitrogen charged back head for superior energy transfer
- Large diameter piston for increase in impact energy
- CD designed threads on through-bolt provide even load distribution and greater surface contact between the nut and bolt
- New front head design includes replaceable thrust bushing for added service life



		F6BHL	F6LN	F6FT	F9LN
Operating weight, P&B	kg	365			
Operating weight, FT ¹⁾	kg			350	
Operating weight, LN ²⁾	kg		365		535
Height with rod, pin and bush	mm	1450			
Height with rod, LN	mm		1400		1565
Height with rod, FT	mm			1450	
Operating pressure	min	MPa	10	10	10
	max		16	16	17
Oil flow	min	l/min	50	50	50
	max		150	150	150
Impact rate (frequency)	min	bpm	650	650	400
	max		1600	1600	1400
Impact energy	joule		884	884	1305
Rod diameter Ø	mm		75	75	90
Effective rod length	mm		450	450	500
Weight rod (standard)	kg		21,5	21,5	35,5
Hose inner dia Ø Press. Return	mm		12	12	19
Base machine weight	ton		3,5 - 10	5,0-9,0	6,0-12

¹⁾ Operating weight with top bucket. ²⁾ LN Silent Version = Sound and vibration damping
Specifications subject to change without notice



WHERE EXPERIENCE COUNTS